

## FRESCOLORI® marroc

Delivery and servicing surfaces exclusively by trained FRESCOLORI processing specialists, with a long-term guarantee of high quality.

The hidden treasure - a pearl: with its cool, calm and yet very lively elegance. With an extremely thin smoothness optics, but a powdery-soft feel. Marroc sleekly enhances the surface and creates a dreamy feeling.

## FRESCOLORI® marroc

Material:	2 CM3 layers Wax
Consumption:	CM3 about 1,0 kg/m <sup>2</sup> each layer Wax, about 0,06 kg/m <sup>2</sup>
Colour:	freely selectable
Application:	Indoor

Surfaces are prepared and primed.

- Application of the first layer of the Caramor limestone-marble plaster, in grain thickness 3
- Observe the waiting times, with a rest period until the first layer is half dry.
- Application of the second layer of the Caramor limestone-marble plaster, in grain thickness 3
- Observe the quite short waiting time (touch dry)
- Humidify the surface with a long bristle brush/spray bottle with water, and prevent any running of the water on the surface
- Instant smooth the surface with a trowel, by applying a uniform pressure
- Observe the uniform distribution of the effluent limestone milk
- Design freedom: light or strong smoothing of the surface
- After short drying, polish with a trowel
- Carefully sand the corners and edges the next day
- Apply the wax with a trowel
- Polish the surface with a polishing machine, provided with a lambskin covered disk, and sand after a waiting period of approx. 1 hour.