

FRESCOLORI® MARANZO® preparation

Adhesion and primer dispersion for soil

Primer, adhesive bridge and pore closure with water-repellent effect prevent the rising of air bubbles from the substrate when applying the coats. Install stainless steel termination rails with a special adhesive and separately reinforce the inner edge.

Floor levelling filler

Inside/Outside. Floor. Application of the filler, levelling and smoothing the floor surfaces made of concrete, cement screeds, tiles and paving, as well as of other suitable substrates.

Adhesion and primer dispersion for soil

Primer, adhesive bridge and pore closure with water-repellent effect prevent the rising of air bubbles from the substrate when applying the coats.

FRESCOLORI® MARANZO® shower preparation

Adhesion and primer dispersion for soil

Primer, adhesive bridge and pore closure with water-repellent effect prevent the rising of air bubbles from the substrate when applying the coats. Make the slope for the shower floor.

Adhesion and primer dispersion for soil

Primer, adhesive bridge and pore closure with water-repellent effect prevent the rising of air bubbles from the substrate when applying the coats.

Reinforce and seal the floor surfaces with sealing compound

Apply two spatula spreads with a smoothing consistency, with a dry film thickness of at least 2 mm. Apply the sealing compound with the notched trowel, embed in a fabric towel, and press it using a spatula. After drying, retouch the surface a second time with the sealing compound.

FRESCOLORI® smoothing of the pre-applied layer of plaster (EP)

FRESCOLORI® MARANZO® Design

If required:

FRESCOLORI® Pre-plaster levelling EP

FRESCOLORI® Maranzo EP onto the prepared floor surfaces marble plaster. After drying, apply an intermediate coat of EP primer. After renewed drying, apply the next layer and shape.

With the Maranzo surface, waves and slight differences in colour tone are the hallmark and idea; these are part of the appearance of the floor. A special feature of the technique is that the surface does not always have the same structure. Deviations from the sample surface are possible and the respective "handwriting" of the processor. Maranzo can be compared to a parquet floor in terms of surface stress.

After completion, any damage to the surface should be repaired promptly to avoid stains.

FRESCOLORI® Sealer

Water-based, silk matt/glossy, transparent and 2-component sealer with good chemical resistance.