

FRESCOLORI® concrete

Delivery and servicing surfaces exclusively by trained FRESCOLORI® processing specialists, with a long-term guarantee of high quality.

Concrete-like surface design, with a tension which results from the interplay between the smooth properties of the material, and its structured, dense and porous radiation. A timeless modern wall design, which can vary depending on the execution, in producing its smooth, structured and thus massive and stable effect.

Material:	2 CM5K layers ETC, if needed
Consumption:	CM5K about 2.4 kg/m ² each layer ETC about 150 ml/m ² , if needed
Colour:	freely selectable
Application:	Indoor

Surfaces are prepared and primed.

- Application of the first layer of the CARAMOR® limestone-marble plaster, in grain thickness 5, with added marble granules
- Respect the waiting times with a rest period until the next day
- Application of the second layer of the CARAMOR® limestone-marble plaster, in grain thickness 5, with blended marble granules
- Carry out direct structuring during application
- Observe the quite short waiting time (touch dry)
- Humidify the surface with a long bristle brush/spray bottle with water, and prevent any running of the water on the surface
- Instant smooth the surface with a trowel, by applying a uniform pressure
- Observe the uniform distribution of the effluent limestone milk
- Design freedom: light or strong smoothing of the surface
- If necessary, re-soak the excess of limestone milk after drying, with the brush (surface should be smoother after drying.)
- Protect with ETC, if necessary