

## **FRESCOLORI® concrete Five S**

Delivery and servicing surfaces exclusively by trained FRESCOLORI® processing specialists, with a long-term guarantee of high quality.

Concrete Five S, an extension of our concrete surface, obtained by adding additional coarse marble granules. A spatial experience of the concrete surface. The tensioned interaction of the opposites – cold and warm, smooth and structured, dense and porous. An individual statement, a space statement: timeless modernity, solid and stable. An effect that cannot be more immediate than now.

<b>Material:</b>	2 CM5K layers ETC
<b>Consumption:</b>	CM5K about 2.4 kg/m <sup>2</sup> each layer ETC, about 0.08kg/m <sup>2</sup>
<b>Colour:</b>	freely selectable
<b>Application:</b>	Indoor

Surfaces are prepared and primed.

- Application of the first layer of the CARAMOR® limestone-marble plaster, in grain thickness 5, with added coarse marble granules
- Respect the waiting times with a rest period until the next day
- Application of the second layer of the CARAMOR® limestone-marble plaster, in grain thickness 5, with added coarse marble granules
- Direct structuring during application, alternatively with the aid of easy application of the material
- Observe the quite short waiting time (touch dry)
- Humidify the surface with a long bristle brush/spray bottle with water, and prevent any running of the water on the surface
- Instant smooth the surface with a trowel, by applying a uniform pressure
- Observe the uniform distribution of the effluent limestone milk
- Respect a waiting time of one day (until the next day)
- Polish the surface with the polishing machine (grain size 180)
- Apply the ETC protection with a brush