

FRESCOLORI® grained

Delivery and servicing surfaces exclusively by trained FRESCOLORI® processing specialists, with a long-term guarantee of high quality.

A wall surface with evenly smooth radiance – natural open-pore structure, accentuated with coloured marble powder. The soaped surface provides an easy protection of the surface.

Material:	2 CM5F layers Soap
Consumption:	CM5 about 2.0 kg/m ² each layer Soap, about 0.06 kg/m ²
Colour:	freely selectable
Application:	Indoor

Surfaces are prepared and primed.

- Application of the first layer of the CARAMOR® limestone-marble plaster, in grain thickness 5, with added coloured marble
- Observe the waiting times, with a rest period until the first layer is dry.
- Application of the second layer of the CARAMOR® limestone-marble plaster, in grain thickness 5, with coloured marble
- Observe the quite short waiting time (touch dry)
- Humidify the surface with a long bristle brush/spray bottle with water, and prevent any running of the water on the surface
- Design freedom: light or strong smoothing of the surface
- Observe the uniform distribution of the effluent limestone milk
- Respect the waiting times with a rest period until the next day
- With a polishing machine (grain size 180)
- Apply the soap with a brush
- Peel off the surface with a trowel
- Observe the waiting time of 2 hours
- Repeat application of the soap with a brush
- Polish the surface with a polishing machine, provided with a lambskin covered disc, and sand after a waiting period of approx. 3 hours.