

FRESCOLORI® metal

Delivery and servicing surfaces exclusively by trained FRESCOLORI® processing specialists, with a long-term guarantee of high quality.

A wall design with a fine light structure combined with a metallic surface. The surface of the light is reflected by the glossy surface.

Material:	2 CM5 layers 2 Sealer-Gel Metal layers
Consumption:	CM5 about 1,8 kg/m ² each layer Sealer Gel Metal about 0.4 kg/m ² per layer
Colour:	freely selectable
Application:	Indoor

Surfaces are prepared and primed.

- Application of the first layer of the CARAMOR® limestone-marble plaster, in grain thickness 5, coverage application
- Observe the waiting times, with a rest period until the first layer is dry.
- Application of the second layer of the CARAMOR® limestone-marble plaster, in grain thickness 5, somewhat slightly structured
- Observe the quite short waiting time (touch dry)
- Humidify the surface with a long bristle brush/spray bottle with water, and prevent any running of the water on the surface
- Instant smooth the surface with a trowel, by applying a uniform pressure
- Observe the uniform distribution of the effluent limestone milk
- Design freedom: light or strong smoothing of the surface
- Observe the waiting times, with a rest period until the second layer is dry.
- Spread the sealer gel with metal pigments (1 - 2 times)
- Observe the waiting time of 1 hour
- Spread the sealer gel with metal pigments
- Observe the waiting times, until the sealer gel is dry
- Polish the surface with a polishing machine provided with a felt covered disc