

## **FRESCOLORI® spatula**

Delivery and servicing surfaces exclusively by trained FRESCOLORI® processing specialists, with a long-term guarantee of high quality.

Spatula – Our lively gem! The fine-grained CARAMOR® limestone-marble plaster is applied to this surface in a high gloss aspect. The light reflects on the smooth surface and makes it appear subtle and delicate. The aliveness is obtained by the final staining of the last Caramor layer (application in spots).

<b>Material:</b>	3 CM1 layers 1 – 2 layers of wax (depending on the shade)
<b>Consumption:</b>	CM1 about 0.8 kg/m <sup>2</sup> each layer Wax about 0.06 kg/m <sup>2</sup> each layer
<b>Colour:</b>	freely selectable
<b>Application:</b>	Indoor

Surfaces are prepared and primed.

- Application of the first layer of the CARAMOR® limestone-marble plaster, in grain thickness 1, coverage application
- Observe the waiting times, with a rest period until the first layer is dry.
- Application of the second layer of the CARAMOR® limestone-marble plaster, in grain thickness 1, a somewhat tighter application
- Observe the quite short waiting time (surface drying)
- Application of the third layer of the CARAMOR® limestone-marble plaster, in grain thickness 1, application in spots
- Carefully sand the corners and edges the next day
- Apply the wax with a trowel
- Observe the waiting times, with a rest period until the wax is dry.
- Apply the second layer of the wax, if necessary with a cotton rag
- Polish the surface with a polishing machine provided with a lambskin covered disc