

FRESCOLORI® stone

Delivery and servicing surfaces exclusively by trained FRESCOLORI® processing specialists, with a long-term guarantee of high quality.

A fascination in stone – matte and puristic, concentrated on the essentials: the expression of an aesthetic lifestyle, a natural atmosphere and a striking spatial effect. What else could better provide for a similar sensory experience of protection and security?

Material:	1 CM7 layer 1 CM7G layer ETC
Consumption:	CM7 about 1.2 kg/m ² each layer CM7G about 1.8 kg/m ² each layer ETC, about 0.08 kg/m ²
Colour:	freely selectable
Application:	Indoor

Surfaces are prepared and primed.

- Application of the first layer of the CARAMOR® limestone-marble plaster, in grain thickness 7
- Observe the waiting times, with a rest period until the first layer is dry.
- Application of the second layer of the CARAMOR® limestone-marble plaster, in grain thickness 7, with added mica
- Observe the quite short waiting time (touch dry)
- Humidify the surface with a long bristle brush/spray bottle with water, and prevent any running of the water on the surface
- Instant smooth the surface with a trowel, by applying a uniform pressure
- Observe the uniform distribution of the effluent limestone milk
- Respect the waiting times with a rest period until the next day
- Surface with polishing machine (grain size 180)
- Application of the ETC protection with a brush
- Polish the surface with a polishing machine provided with a lambskin covered disc